

GasAlertMicro 5

H₂S, CO, O₂, SO₂, PH₃, NH₃, NO₂,
HCN, Cl₂, ClO₂, O₃ and Combustibles

Five-Gas Detector



ACTUAL SIZE



GasAlertMicro 5 with integrally attached pump

Water
Resistant



Optional rechargeable battery and slip-in cradle charger

Protect Yourself

- △ Continuous LCD shows simultaneous gas concentrations for five gases
- △ Smaller and over 50% lighter than competitive instruments
- △ Water-resistant design with an integral concussion-proof enclosure
- △ Integral motorized pump option for remote sampling
- △ Two power options: AA alkaline or rechargeable hot-swappable battery packs
- △ Provides 95 dB alarm tone and two bright wide-angled alarm bars
- △ Equipped with internal vibrating alarm for high noise areas
- △ Multi-language support in English, French, German, Spanish and Portuguese
- △ Three backlight options: standard—activates in low light (auto), in alarm (auto) and reactivates on-demand; alarm only—activates in alarm conditions and reactivates on-demand; stealth mode—deactivated
- △ Four alarm levels: instantaneous Low and High Alarm for all gases; TWA (time-weighted average) and STEL (short-term exposure limit) for toxic gases
- △ Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- △ Records TWA, STEL and maximum exposures to gas and displays readings on command
- △ User selectable field options include: language selection, confidence beep, span level, set TWA/STEL calculation choice, set calibration due date, passcode protection, latching alarm, "SAFE" display function, stealth mode and selectable ppm resolution for some gases (e.g. SO₂ 0.1 ppm)
- △ Full function self-test of: sensor, battery and circuit integrity; and audible/visual alarms



ATEX



and others

Ordering Information

GasAlertMicro 5 is delivered ready for use with sensors (as specified), sensor compartment cover for diffusion operation, battery (as specified), stainless steel alligator belt clip, calibration hose/cap, instructions in local languages and interactive training CD.

Battery/Charger Options

Three AA alkaline batteries
Rechargeable battery pack and desktop/wall mountable slip-in cradle charger.

User-Downloadable Datalogger Option

Datalogging versions include a memory card, software and an IR port for use with the MicroDock II automated calibration and test station.

Pump Option

Includes detector, standard accessories plus integrally attached motorized pump and cover (installed), 12 in./30 cm sample probe with hydrophobic barrier (water trap) and particulate filters, 5 ft./1.5 m sampling tubing, three spare particulate filters and one spare water trap filter.

Value Added Confined Space Kits

Kits include detector, standard accessories plus a hard-sided, foam-lined carrying case, 10 ft./3 m sampling hose, sample probe, battery power (as specified), 34 L calibration gas cylinder(s) with regulator(s).

Accessories

USB Memory Card Reader Vehicle Charger
Manual Aspirator Pump Carrying Holster
MicroDock II—Automatic Calibration and Test Station

www.gasmonitors.com

e-mail: info@bwt.net

GasAlertMicro 5

H₂S, CO, O₂, SO₂, PH₃, NH₃,
NO₂, HCN, Cl₂, ClO₂, O₃
and Combustibles

Five-Gas Detector

GasAlertMicro 5 portable gas detector simultaneously monitors and displays up to five potential atmospheric hazards including oxygen, combustible gases and a range of toxic gases. Compact and lightweight, GasAlertMicro 5 adds multi-gas detection to BW Technologies' water-resistant line of detectors. Audible, visual and vibrator alarms activate in the event of a low, high, TWA or STEL alarm condition. An optional motorized pump is available.

Beyond features that come standard with BW portable instruments such as confidence beep, full function self-test, automatic calibration and passcode protection, GasAlertMicro 5 offers an extended selection of user-settable field options now including: stealth mode, backlight options, selectable ppm resolution, STEL / TWA measurement choice, combustible correction factor options, user-settable calibration gas concentrations and multi-language support.



For further information:

1-888-749-8878	USA
1-800-663-4164	Canada
+44 (0)1295 700 300	Europe
+33 (0) 442 98 17 70	France
+971-4-8871766	Middle East
+61-3-9464-2770	Australia
+86 10 6786 7305	China
+65 6748 4915	South East Asia
+1-403-248-9226	Other Countries

Corporate Headquarters

2840 - 2 Avenue S.E.
Calgary, AB, Canada T2A 7X9
Phone: 1-403-248-9226
Fax: 1-403-273-3708

E-mail: info@bwt.net.com
www.gasmonitors.com

BW1078-01-01-00-8.25x11-20060222-5612-11
© 2007 Honeywell International Ltd. All Rights Reserved.

SPECIFICATIONS

DETECTOR: 1, 2, 3, 4 or 5-gas detector

Gas	Measuring Range	Default Resolution	High Resolution	TWA	STEL	LOW	HIGH
H ₂ S	0-500 ppm	1.0 ppm	0.1 ppm	10	15	10	15
CO	0-999 ppm	1.0 ppm	N/A	35	50	35	200
TwinTox (H ₂ S)	0-500 ppm	1.0 ppm	0.1 ppm	10	15	10	15
TwinTox (CO)	0-500 ppm	1.0 ppm	N/A	35	50	35	200
O ₂	0-30.0%	0.50%	N/A	N/A	N/A	19.5	23.5
SO ₂	0-150 ppm	1.0 ppm	0.1 ppm	2	5	2	5
PH ₃	0-5.0 ppm	1.0 ppm	0.1 ppm	0.3	1.0	0.3	1.0
NH ₃	0-100 ppm	1.0 ppm	0.1 ppm	25	35	25	50
NO ₂	0-99.9 ppm	1.0 ppm	0.1 ppm	2.0	5.0	2.0	5.0
HCN	0-30.0 ppm	1.0 ppm	0.1 ppm	4.7	10.0	4.7	10.0
Cl ₂	0-50.0 ppm	1.0 ppm	0.1 ppm	0.5	1.0	0.5	1.0
ClO ₂	0-1.00 ppm	0.1 ppm	0.01 ppm	0.1	0.3	0.1	0.3
O ₃	0-1.00 ppm	0.1 ppm	0.01 ppm	0.1	0.1	0.1	0.1
Combustible gases	0-100% LEL 0-5.0% v/v	1% 0.1%	N/A	N/A	N/A	10% 0.5%	20% 1.0%

Auto zero: Yes
Calibration: Automatic
Backlight: Standard Mode: low light (auto); alarm condition (auto); reactivation on demand
Alarm Only Mode: alarm condition (auto); reactivation on demand
Stealth Mode: backlight inactive; audible and visual alarms silenced
Sensor: Plug-in, electrochemical cell (toxic and oxygen); catalytic (LEL)
User field options: Confidence beep, set STEL period, force calibration on start-up, enable / disable sensor, passcode protection, latching alarms, span level, passed calibration user-lockout option, "SAFE" display function, stealth mode, fast pump, oxygen auto-cal on start-up, alarm only backlight mode, combustible gas measurement (% LEL or % by volume methane), LCD language option, STEL calculation choice, TWA calculation choice, combustible correction factor options, user-settable calibration gas level, high resolution, clock

ALARM INDICATORS: Clearly advises alarm conditions with audible, visual and vibrator alarms
Visual alarms: Two flashing alarm bars visible from all angles
LCD indicates gas present and alarm levels encountered
Audible alarm: Typically 95 dB at 1 ft. / 30 cm variable pulsed audible alarm
Vibrator alarm: Pulses warning in gas alarm conditions or for any status alarms
Status alarms: Low battery, over range, multiple gas / pump and failed or missing sensor
ALARM LEVELS: Instantaneous Low Alarm for all gases; Instantaneous High Alarm for all gases; TWA (time-weighted average) and STEL (short-term exposure limit) for toxics, OL (over alarm) for LEL

LCD: Continuous, alphanumeric gas readout and status display advises: H₂S, CO, O₂, SO₂, PH₃, NO₂, NH₃, HCN, Cl₂, ClO₂, O₃, and/or combustibles (0-100% LEL or 0-5.0% methane)
Gas concentration: Simultaneously and continuously displays gas concentration(s) for all sensors (in ppm, % LEL or % v/v)
Peak (MAX)/STEL/
TWA ppm: Records exposures and displays on demand
Alarm setpoints: Displayed on activation and on demand
Calibration due date: Days remaining on start-up
Clock: Real-time clock setting displayed on start-up

TESTS: Full function self-test: Sensor integrity, circuitry, battery and audible/visual alarms on activation
Battery: Continuous

GENERAL SPECIFICATIONS: Rugged, composite material; two-shot molded polymer case with integral anti-shock boot
Operating temperature: -4 to 122°F / -20 to 50°C
Humidity: 0 - 95% RH (non-condensing)
EMI/RFI: Complies with EMC Directive 89/336/EEC
Protection: Highly water resistant and dust proof housing
Battery Options: 23 hours on three AA alkaline cells or 20 hours on rechargeable "hot-swappable" battery pack when equipped with oxygen, combustible, TwinTox (H₂S/CO) and one additional toxic sensor

Size: 5.7 x 2.9 x 1.5 in. / 14.5 x 7.4 x 3.8 cm
Weight: 13.1 oz. / 370 g

WARRANTY: Full 2-year warranty including all sensors (1 year NH₃ sensor)

DATALOGGER OPTIONS: User-downloadable datalogger
Data recorder: All events and occurrences (calibration zero adjustment, calibration span adjustment, gas readings, TWA, STEL, alarm condition, failures detected by the microprocessor). Factory set at 5-second intervals and user-settable from 1 to 127-second intervals
4 months of continuous data at 5 second intervals via memory card; when full, the wrap-around feature replaces oldest data with most recent data

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

RATINGS AND CERTIFICATIONS: Class I, Div. 1, Gr. A, B, C, D
(Intrinsic safety) American Bureau of Shipping

ATEX: CE II 1 G T4
EEx ia IIC T4
IECEx: Ex ia IIC T4

Locally distributed by:

MSS Pump, Seal & Safety
T: 08 8254 9450 F: 08 8125 6638
www.mssonline.com.au